

Reax top

P/N: 036130000



The classic with 5 mm shaking orbit

This model is particularly suitable for simple mixing tasks. In short-term operation mode, the shaking motion is triggered by pressure on the test tube tray. This mode is suitable for mixing up solutions, for example.

Persistent cell pellets can be dissolved gently but powerfully in continuous operation. With a speed of up to 3.200 rpm and a shaking orbit of 5 mm, reliable and uniform distribution of solids, and homogenization of highly viscous media are guaranteed.

Reax top - Technical Data

| | |
|---------------------------------------|--|
| Overheat protection | self-resetting |
| Permissible ambient conditions | 5 - 31 °C at 80 % rel. humidity 32 - 40 °C decreasing linearly up to max. 50 % rel. humidity |
| Weight | 2.8 kg |
| Protection class (EN 60529) | IP 22 |
| Timer | - |
| Rotation speed range | 200 - 3,200 rpm |
| Power input | 51 |
| Dimensions (w/d/h) | 134 x 172 x 105 mm |
| Max. Load | - |
| Operating Mode | automatic or continuous |
| Rotation speed setting | analog |
| Orbit / Stroke | 5 mm |
| Platform size | - |
| Accessories included | - |
| Angle | - |
| Motion | vibrating |
| Ambient temperature range (operation) | - |
| Ambient temperature range (storage) | - |
| Interfaces | - |
| Usable area | - |
| Installation altitude | - |